

Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 1/10

STAK A340

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: U051150004
Product name STAK A340

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended use
Solvent free silicone release agent.
Uses advised against:
Different uses than those intended.

1.3. Details of the supplier of the safety data sheet

Name CENTRO DISTRIBUZIONE UTENSILI SCPA

Full address Via delle Gerole, 19
District and Country 20867 CAPONAGO (MB)

ITALY

tel. +39 02 95746081 fax. + 39 02 95745182

e-mail address of the competent person

responsible for the Safety Data Sheet info@cdu.net

Product distribution by: Centro Distribuzione Utensili Scpa

1.4. Emergency telephone number

For urgent inquiries refer to +39 02 95746081 during office hours 8.30-12.30 - 13.30-17.30.

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: DANGER

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

Precautionary statements:

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 2/10

STAK A340

P211 P251 Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant.

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

PROPANE

CAS 74-98-6 50 ≤ x < 60 Flam. Gas 1 H220, Press. Gas (Lig.) H280, Classification note according to

Annex VI to the CLP Regulation: U

EC 200-827-9

INDEX 601-003-00-5

Reg. no. 01-2119486944-21

BUTANE

CAS 106-97-8 25 \leq x < 30 Flam. Gas 1 H220, Press. Gas (Liq.) H280, Classification note according to

Annex VI to the CLP Regulation: C U

EC 203-448-7

INDEX 601-004-00-0

Reg. no. 01-2119474691-32

ISOBUTANE

CAS 75-28-5 10 ≤ x < 12,5 Flam. Gas 1 H220, Press. Gas H280, Classification note according to Annex

VI to the CLP Regulation: C U

EC 200-857-2

INDEX 601-004-00-0

Reg. no. 01-2119485395-27

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

SECTION 4. First aid measures

4.1. Description of first aid measures

No episodes of harm to the staff authorised to use the product have been reported. The following general measures should be adopted as necessary: INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention. INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Do not give anything by mouth to an unconscious person. EYES and SKIN: Wash with plenty of water. In the event of persistent irritation, get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatically treatment.



Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 3/10

STAK A340

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany): 2B

7.3. Specific end use(s)

Solvent free silicone release agent.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU Deutschland TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte DNK Danmark Graensevaerdier per stoffer og materialer



Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

Page n. 4/10

STAK A340

ESP España FIN Suomi

INSHT - Límites de exposición profesional para agentes químicos en España 2017 HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveysministeriön julkaisuja

2012:5

FRA France

POL ROU JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

GBR United Kingdom NLD Nederland

Polska

România

EH40/2005 Workplace exposure limits Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18

ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r Monitorul Oficial al României 44; 2012-01-19

TLV-ACGIH **ACGIH 2018**

PROPANE										
Threshold Limit Value										
Туре	Country	TWA/8h		STEL/15min						
		mg/m3	ppm	mg/m3	ppm					
AGW	DEU	1800	1000	7200	4000					
MAK	DEU	1800	1000	7200	4000					
TLV	DNK	1800	1000							
HTP	FIN	1500	800	2000	1100					
NDS	POL	1800								
TLV	ROU	1400	778	1800	1000					
TLV-ACGIH			1000							

BUTANE										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15min						
		mg/m3	ppm	mg/m3	ppm					
AGW	DEU	2400	1000	9600	4000					
MAK	DEU	2400	1000	9600	4000					
TLV	DNK	1200	500							
VLA	ESP		1000							
HTP	FIN	1900	800	2400	1000					
VLEP	FRA	1900	800							
WEL	GBR	1450	600	1810	750					
OEL	NLD	1430								
NDS	POL	1900		3000						
TLV-ACGIH			1000							

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold

ΕN



Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 5/10

STAK A340

values considered. The protection provided by masks is in any case limited. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance clear liquid Colour colourless Odour odourless Odour threshold Not applicable Not applicable Melting point / freezing point Not available Initial boiling point Not applicable Boiling range Not available Flash point < 0 °C Evaporation Rate Not available Flammability of solids and gases Not applicable Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density 0,9 kg/l

Solubility in water: insoluble
Partition coefficient: n-octanol/water
Auto-ignition temperature
Decomposition temperature
Viscosity
Not available
Explosive properties
Oxidising properties
Not applicable
Not applicable
Not applicable

9.2. Other information

VOC (Directive 2010/75/EC): 100,00 % - 537,03 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.



Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 6/10

STAK A340

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

Information on likely routes of exposure

Information not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

Interactive effects

Information not available.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)
LD50 (Oral) of the mixture:

Not classified (no significant component)
LD50 (Dermal) of the mixture:

Not classified (no significant component)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available.

12.2. Persistence and degradability



Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 7/10

STAK A340

BUTANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

PROPANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water 1,09

PROPANE

Partition coefficient: n-octanol/water 1,09

12.4. Mobility in soil

Information not available.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1





Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 8/10

STAK A340

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: Limited Quantities: 1 L Tunnel restriction code: (D)

Special Provision: -

IMDG: EMS: F-D, S-U

IATA: Cargo: Maximum quantity: 150 Kg Packaging inst

Pass.: Maximum quantity: 75 Kg

Limited Quantities: 1 L

Special Instructions: A145, A167, A802

Packaging instructions: 203

Packaging instructions: 203

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant.

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None

Healthcare controls

TKM CHEM

CENTRO DISTRIBUZIONE UTENSILI SCPA

Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

Page n. 9/10

STAK A340

Information not available.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017) WGK 1: Low hazard to waters.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1 Flammable gas, category 1

Aerosol 1 Aerosol, category 1 Aerosol 3 Aerosol, category 3 Press. Gas (Liq.) Liquefied gas Press. Gas Pressurised gas

H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may burst if heated.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament

ΕN



Revision nr. 5 Dated 07/08/2019

Printed on 07/08/2019

ΕN

Page n. 10/10

STAK A340

- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified: 01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.