


Acciaio
<850
N/mm²

<850 N/mm² - METRICO PASSO GROSSO - ESECUZIONE LUNGA



A05085



Tkn

| | |
|-------------------------|------------|
| Norma | Norma Int. |
| Tolleranza | ISO 2 6H |
| Rivestimento | TiN |
| Materiale | HSS-E |
| Destro / Sinistro | Destro |
| Angolo elica | 40° |
| Imbocco | |
| Emulsione / Olio | E 0 |
| Cieco / Passante | ≤ 3xd |
| Vc min / Vc max (m/min) | 10 / 25 |
| Vc min / Vc max (m/min) | 6 / 10 |
| Vc min / Vc max (m/min) | |
| Vc min / Vc max (m/min) | |
| Vc min / Vc max (m/min) | 10 / 20 |
| Vc min / Vc max (m/min) | 5 / 15 |
| Vc min / Vc max (m/min) | |

| M | Passo (mm) | Preforo (mm) | ø d2 (mm) | □ (mm) | L1 (mm) | L2 (mm) | Finale Codice | A05085 TiN € |
|-----|------------|--------------|-----------|--------|---------|---------|---------------|--------------------|
| M3 | 0,5 | 2,5 | 3,5 | 2,7 | 112 | 6 | 0030 | |
| M4 | 0,7 | 3,3 | 2,8 | 2,1 | 112 | 7,5 | 0040 | |
| M5 | 0,8 | 4,2 | 3,5 | 2,7 | 125 | 8,5 | 0050 | |
| M6 | 1 | 5 | 4,5 | 3,4 | 125 | 11 | 0060 | |
| M8 | 1,25 | 6,8 | 6 | 4,9 | 140 | 14 | 0080 | |
| M10 | 1,5 | 8,5 | 7 | 5,5 | 160 | 16 | 0100 | |
| M12 | 1,75 | 10,2 | 9 | 7 | 180 | 18,5 | 0120 | |