



Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **U05140**
Product name: **CUT OIL F500**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Universal cutting fluid.**
Uses advised against: **Different uses than those intended.**

1.3. Details of the supplier of the safety data sheet

Name: **CENTRO DISTRIBUZIONE UTENSILI SCPA**
Full address: **Via delle Gerole, 19**
District and Country: **20867 CAPONAGO (MB)**
ITALY
tel. **+39 02 95746081**
fax. **+ 39 02 95745182**

e-mail address of the competent person responsible for the Safety Data Sheet
Product distribution by:

info@cdu.net
Centro Distribuzione Utensili Scpa

1.4. Emergency telephone number

For urgent inquiries refer to **+39 02 95746081 during office hours 8.30-12.30 - 13.30-17.30.**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.
Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH210 Safety data sheet available on request.
EUH208 Contains: SULFONIC ACIDS, PETROLEUM, CALCIUM SALTS;
BENZENESULFONIC ACID, MONO-C16-24-ALKYL DERIVS., CALCIUM SALTS;
BENZENESULFONIC ACID, C10-16-ALKYL DERIVS., CALCIUM SALTS.
May produce an allergic reaction.

Precautionary statements: --

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.



CUT OIL F500

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	X = Conc. %	Classification 1272/2008 (CLP)
----------------	-------------	--------------------------------

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

CAS 64742-65-0

58 ≤ x < 63

Substance with extract content in DMSO less than 3% by weight, determined with IP 346 method. Classification note according to Annex VI to the CLP Regulation: L

EC 265-169-7

INDEX 649-474-00-6

Reg. no. 01-2119471299-27

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

CAS -

14,5 ≤ x ≤ 19,5

Asp. Tox. 1 H304, EUH066

EC 918-481-9

INDEX -

Reg. no. 01-2119457273-39

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatically treatment.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained

	CENTRO DISTRIBUZIONE UTENSILI SCPA	Revision nr. 6 Dated 16/10/2019 Printed on 16/10/2019 Page n. 3/9 Replaced revision:5 (Dated: 08/08/2019)	EN
	CUT OIL F500		
Safety Data Sheet		According to Annex II to REACH - Regulation 2015/830	

open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 10

7.3. Specific end use(s)

Universal cutting fluid.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

TLV-ACGIH

ACGIH 2019

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
TLV-ACGIH		5		10	INHAL

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.



CUT OIL F500

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	clear liquid
Colour	ochre
Odour	characteristic
Odour threshold	Not available
pH	Not applicable
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	79,5 °C (closed cup ASTM D 93)
Evaporation Rate	Not available
Flammability of solids and gases	Not applicable
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,87 - 0,88 Kg/l (20°C)
Solubility	in water: insoluble; in acetone: soluble
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	36 cSt (40°C)
Explosive properties	Not available
Oxidising properties	Not available

	CENTRO DISTRIBUZIONE UTENSILI SCPA	Revision nr. 6 Dated 16/10/2019 Printed on 16/10/2019 Page n. 5/9 Replaced revision:5 (Dated: 08/08/2019)	EN
	CUT OIL F500		
Safety Data Sheet		According to Annex II to REACH - Regulation 2015/830	

9.2. Other information

VOC (Directive 2010/75/EC) : 82,05 % - 720,24 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Forms explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

Avoid exposure to: sources of heat, naked flames, light, ignition sources.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Avoid exposure to: heat, sparks, flames, ignition sources, electrostatic discharges.

10.5. Incompatible materials

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

Incompatible with: strong acids, strong bases, oxidising agents.

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Incompatible with: strong oxidising agents.

10.6. Hazardous decomposition products

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

When heated to decomposition releases: carbon monoxide, carbon dioxide, harsh fumes.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

Information on likely routes of exposure

Information not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

Interactive effects

Information not available.



CUT OIL F500

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: Not classified (no significant component)
LD50 (Oral) of the mixture: Not classified (no significant component)
LD50 (Dermal) of the mixture: Not classified (no significant component)

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC

LD50 (Oral) > 5000 mg/kg Rat (OECD 401)
LD50 (Dermal) > 5000 mg/kg Lapin (OECD 402)
LC50 (Inhalation) > 5000 mg/m3 Rat (OECD 403)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

LD50 (Oral) > 5000 mg/kg Rat (OCSE 401)
LD50 (Dermal) > 5000 mg/kg Rat (OECD 402)
LC50 (Inhalation) > 5000 mg/m2/4h Rat (OCSE 403)

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

SULFONIC ACIDS, PETROLEUM, CALCIUM SALTS;
BENZENESULFONIC ACID, MONO-C16-24-ALKYL DERIVS., CALCIUM SALTS;
BENZENESULFONIC ACID, C10-16-ALKYL DERIVS., CALCIUM SALTS.

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class. Viscosity: 36 cSt (40°C).

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

LC50 - for Fish > 1000 mg/l/96h *Onchorhynchus mykiss*

EC50 - for Crustacea > 1000 mg/l/48h *Daphnia magna*



CUT OIL F500

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

EC50 - for Algae / Aquatic Plants > 1000 mg/l/72h Scenedesmus subspicatus

12.2. Persistence and degradabilityDISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC
Solubility in water NegligibleHYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS
Solubility in water Insoluble

Rapidly degradable 80 % - 28d

12.3. Bioaccumulative potentialDISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC
Partition coefficient: n-octanol/water > 3,5HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS
Partition coefficient: n-octanol/water > 4 Log Kow**12.4. Mobility in soil**

Information not available.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.



CUT OIL F500

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

14.5. Environmental hazards

Not applicable.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant.

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Seveso Category - Directive 2012/18/EC: None.Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls

Information not available.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the mixture.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Asp. Tox. 1	Aspiration hazard, category 1
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road

- CAS NUMBER: Chemical Abstract Service Number



CUT OIL F500

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 06 / 07 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16