

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **U052350004**
Product name: **VASELINEGREASE G320**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Vaseline grease.**
Uses advised against: **Different uses than those intended.**

1.3. Details of the supplier of the safety data sheet

Name: **CENTRO DISTRIBUZIONE UTENSILI SCPA**
Full address: **Via delle Gerole, 19**
District and Country: **20867 CAPONAGO (MB)**
ITALY
tel. **+39 02 95746081**
fax. **+ 39 02 95745182**

e-mail address of the competent person

responsible for the Safety Data Sheet: **info@cdu.net**
Product distribution by: **Centro Distribuzione Utensili Scpa**

1.4. Emergency telephone number

For urgent inquiries refer to: **+39 02 95746081 during office hour 8.30-12.30 - 13.30-17.30.**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **DANGER**

Hazard statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.

Precautionary statements:

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.



P251
P410+P412

Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant.

3.2. Mixtures

Contains:

Identification

HYDROCARBONS, C3-4

CAS 68476-40-4

EC 270-681-9

INDEX 649-199-00-1

PETROLATUM

CAS 8009-03-8

EC 232-373-2

INDEX -

Reg. no. 01-2119490412-42

WHITE MINERAL OIL (PETROLEUM)

CAS 8042-47-5

EC 232-455-8

INDEX -

Reg. no. 01-2119487078-27

x=Conc. %

Classification 1272/2008 (CLP)

42 ≤ x ≤ 52

Flam. Gas 1 H220, Press. Gas H280, Note K U

14 ≤ x ≤ 24

--

5,2 ≤ x ≤ 7,2

Asp. Tox. 1 H304

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants max: 52,00 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatically treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT



None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

Storage class TRGS 510 (Germany):

2B

7.3. Specific end use(s)

Vaseline grease.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
DNK	Danmark	Graensevaerdier per stoffer og materialer
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FIN	Suomi	HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveystieteiden tutkimuskeskus julkaisu 2012:5
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r

TLV-ACGIH

ACGIH 2016

HYDROCARBONS, C3-4

Threshold Limit Value Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
TLV	DNK	1200	500		
VLA	ESP		800		
HTP	FIN	1900	800	2400	1000
VLEP	FRA	1900	800		
WEL	GBR	1450	600	1810	750
OEL	NLD	1430			
NDS	POL	1900		3000	
TLV-ACGIH			1000		(Alcani, C1.C4)

PETROLATUM

Threshold Limit Value Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
TLV-ACGIH		2			RESP

WHITE MINERAL OIL (PETROLEUM)

Threshold Limit Value Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
AGW	DEU	5		20	RESP
MAK	DEU	5		20	RESP
TLV-ACGIH		5		10	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers
Oral		VND	40 mg/kg bw/d
Inhalation			35 mg/m ³ 160 mg/m ³
Skin			92 mg/kg bw/d 220 mg/kg bw/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter

combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	aerosol
Colour	colourless
Odour	odourless
Odour threshold	Not available
pH	Not applicable
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,65 - 0,75 Kg/l
Solubility	in water: insoluble; in acetone: soluble
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2010/75/EC) :	52,00 %
Propellant flammability	extremely flammable
Limit of propellant flammability	1,8-9,5%

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

HYDROCARBONS, C3-4

May form flammable mixtures with: strong oxidising agents. Forms explosive mixtures with: strong oxidising agents, nitrates.

10.4. Conditions to avoid

Avoid overheating.

HYDROCARBONS, C3-4

Keep away from: strong oxidising agents. Avoid exposure to: sources of heat, naked flames, overheated surfaces, electrostatic discharges.

PETROLATUM

Avoid exposure to: naked flames, heat, light, ignition sources.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

HYDROCARBONS, C3-4

Avoid contact with: strong oxidising agents.

PETROLATUM

Avoid contact with: acids, strong bases, oxidising agents.

10.6. Hazardous decomposition products

Information not available.

SECTION 11. Toxicological information

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled according to good industrial practices.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

Information on likely routes of exposure

Information not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

Interactive effects

Information not available.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

WHITE MINERAL OIL (PETROLEUM)

LD50 (Oral)

> 5000 mg/kg Rat (OECD - 401)

LD50 (Dermal)

> 5000 mg/m³ Rabbit (OECD - 402)

LC50 (Inhalation)

> 5000 mg/kg Rat (OECD - 403)

PETROLATUM

LD50 (Oral)

> 5000 mg/kg Rat (OECD - 401)

LD50 (Dermal)

> 2000 mg/kg Rabbit (OECD - 402)

HYDROCARBONS, C3-4

LC50 (Inhalation)

658 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class.

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

PETROLATUM

LC50 - for Fish

> 100 mg/l/96h Pimephales promelas (OECD - 203)

EC50 - for Crustacea

> 10000 mg/l/48h Daphnia magna (OECD - 202)

HYDROCARBONS, C3-4

LC50 - for Fish

24,11 mg/l/96h (QSAR calculation - butane - ECOSAR Program v1.00)

EC50 - for Crustacea

16,33 mg/l/48h Daphnia (isobutane, calculated with ECOSAR Program v1.00. EPI Suite™ v4.00)

12.2. Persistence and degradability

WHITE MINERAL OIL (PETROLEUM)

Entirely degradable.

PETROLATUM

Solubility in water

Insoluble

HYDROCARBONS, C3-4

Solubility in water

24,4 - 60,4 mg/l

Rapidly degradable.

12.3. Bioaccumulative potential

HYDROCARBONS, C3-4

Partition coefficient: n-octanol/water

2,03058 Log Kow (QSAR, KOWWIN, Butane)

12.4. Mobility in soil

Information not available.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS

IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: -- Special Provision: -	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo: Pass.: Special Instructions:	Maximum quantity: 100 Kg Maximum quantity: 25 Kg A802	Packaging instructions: 130 Packaging instructions: 130

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant.

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Seveso Category - Directive 2012/18/EC: P3aRestrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls

Information not available.

German regulation on the classification of substances hazardous to water (VwVwS 2005)

WGK 3: Severe hazard to waters

15.2. Chemical safety assessment

No chemical safety assessment for the mixture was carried out.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1	Flammable gas, category 1
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Press. Gas	Pressurised gas
Asp. Tox. 1	Aspiration hazard, category 1
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may burst if heated.
H304	May be fatal if swallowed and enters airways.



LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 07 / 08 / 09 / 10 / 11 / 12 / 14 / 15.