











Misura											Coppia max di serraggio (Nm)
	0°	0°	90°	90°	0°-45°	45°-60°	Asimm.	0°-45°	45°-60°	Asimm.	
	1 braccio	2 bracci	1 braccio	2 bracci	2 bracci			3/4 bracci			
300 Kg - M10	0,6	1,2	0,3	0,6	0,42	0,3	0,3	0,63	0,45	0,3	16
500 Kg - M12	1	2	0,5	1	0,75	0,5	0,5	1,1	0,75	0,5	28
1120 Kg - M16	2	4	1,12	2	1,5	1,12	1,12	2,36	1,6	1,12	70
1120 Kg - M20	2	4	1,12	2	1,5	1,12	1,12	2,36	1,6	1,12	135
2000 Kg - M20	4	8	2	4	2,8	2	2	4	3	2	135
3150 Kg - M24	6,3	12,5	3,15	6,3	4,25	3,15	3,15	6,3	4,75	3,15	230
5300 Kg - M30	10,6	21,2	5,3	10,6	7,1	5,3	5,3	11,2	8	5,3	465
8000 Kg - M30	12,5	25	8	16	11,2	8	8	16,8	12	8	465
8000 Kg - M36	12,5	25	8	16	11,2	8	8	16,8	12	8	814
10000 Kg - M42	15	30	10	20	14	10	10	21,2	15	10	1304
15000 Kg - M48	25	50	15	30	21	15	15	31,5	22,5	15	1981
15000 Kg - M56	25	50	15	30	21	15	15	31,5	22,5	15	3000
15000 Kg - M64	25	50	15	30	21	15	15	31,5	22,5	15	4738
25000 Kg - M72	35	70	25	50	35	25	25	52,5	37,5	25	6913
30000 Kg - M80	35	70	30	60	42	30	30	63	45	30	9625
35000 Kg - M90	35	70	35	70	49	35	35	73,5	52,5	35	14000